

**NEW
PRODUCT**

DOSING CONTROL

FOR TIMED APPLICATIONS

The Econ T is a compact, easy to program pump with flexibility to schedule up to 24 separate events within a 7 day period

Each separate event can run from a minimum of 1 minute to a maximum of 23 hours and 59 minutes within each programmed day.

The automatic dosing control is reliable for timed applications including injection of enzymes for drain line maintenance and biocide feed in small cooling towers or water fountains.

Control panel features a 24 hour integral clock that has a battery backup to maintain the time of day.



**0.6 to 21.7 gpd @ 80 psi
2.5 to 15 gpd @ 25 psi**

Wall Mountable

**Simple Programming
with LCD Display**

Effortless Tube Replacement





Econ T is ideal for light duty applications

- Patented quick release pump head design
- Solid one piece tube construction
- UL & cUL listed
- NSF 61 & 372 listed for USA & Canada
- 4 lbs
- 5.3" l x 3.6" w x 5.8" h

Optional Mounting Accessories



Mounting Kit EC303
For Stenner Tank or wall mount



Stand EC304
For horizontal display or wall mount

Outputs

Item Number Prefix	Pump Tube	Roller Assembly	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Pressure psi	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute	Pressure bar
E10T1F	F	White	0.6	0.02	3.0	0.05	80	2.2	0.09	90.0	1.50	5.5
E10T2F	F	White	1.3	0.05	6.6	0.11	80	4.8	0.20	198.0	3.30	5.5
E20T4F	F	White	3.4	0.14	18.0	0.30	80	13.1	0.54	544.8	9.08	5.5
E20T4G	G	Black	12.3	0.51	65.4	1.09	80	46.5	1.94	1937.4	32.29	5.5
E20T4H	H	Black	21.7	0.90	115.2	1.92	80	82.0	3.41	3416.4	56.94	5.5
E10T1A	A	White	2.5	0.10	13.2	0.22	25	9.5	0.39	396.0	6.60	1.7
E10T2A	A	White	5.0	0.21	26.4	0.44	25	18.9	0.79	786.0	13.10	1.7
E10T2B	B	White	8.5	0.35	45.6	0.76	25	32.2	1.34	1338.0	22.30	1.7
E10T2C	C	White	15.0	0.63	79.8	1.33	25	56.8	2.37	2364.0	39.40	1.7

Approximate Maximum Outputs @ 50/60Hz

Build An Item Number

											1	S
--	--	--	--	--	--	--	--	--	--	--	----------	----------

Select **Item Number Prefix** from output chart above

Leave blank if not ordering a tank system

Tank

- S7N** 7.5 Gallon White
- S1N** 15 Gallon White
- S3N** 30 Gallon White

NOTE: Tanks also sold separately.

Voltage & Hertz/Cord

- 7** 120V 60Hz; 6' cord
- 8** 120V 60Hz; 10' cord

Suction & Discharge Tubing

- 1** 1/4" White

Tube Material

- S** Santoprene®

This information is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice. FET 0313



STENNER PUMP COMPANY

Jacksonville, Florida USA

www.stenner.com

© Stenner Pump Company All Rights Reserved



Econ T Manual